




ZONYX TRACK

The Zonyx Track in lengths of 4ft, 6ft and 8ft is made out of anodized aluminum with insulated conductors and copper ground wire. Track is field bendable to a minimum of a 18" radius using bending machine. Each track section includes two (2) insulated end caps that are secured with set screws.



Part Number

- 350004mc
- 350006mc
- 350006-1mc
- 350008mc
- 350008-1mc

Description

- 4'
- 6'
- curved track 5'
- 8'
- curved track 7'

Technical

2400VA maximum
120VAC input
Suitable for dry location only




ZONYX END CAP



Part Number	Description
350020mc	■ end cap



ZONYX TRACK CONNECTOR / ISO CONNECTOR




Part Number	Description
350060mc	■ conductive
350061mc	■ ISO

Technical
 2400VA maximum
 120VAC rated
 Suitable for dry locations only



ZONYX FLEXIBLE TRACK CONNECTOR




Part Number	Description
350065mc	■ flex connector

Technical
 2400VA maximum
 120VAC rated
 Suitable for dry locations only



ZONYX 90° CONNECTOR




Part Number	Description
350062mc	■ 90° connector

Technical
 2400VA maximum
 120VAC rated
 Suitable for dry locations only



ZONYX T CONNECTOR



Part Number

350064mc

Description


■ 3 way connector

Technical

2400VA maximum
120VAC rated
Suitable for dry locations only



ZONYX CROSS CONNECTOR



Part Number


350063mc

Description


■ 4 way connector

Technical

2400VA maximum
120VAC rated
Suitable for dry locations only



ZONYX BENDING MACHINE



Part Number

350099

Description

■ curves track



ZONYX CEILING SUPPORT



Part Number


350110mc

Description

■ 4"



ZONYX ADJUSTABLE CEILING SUPPORT



Part Number	Description
350120mc	■ 7 1/2" - 11 1/2"



ZONYX SUSPENSION SUPPORT


can be field shortened



Part Number	Description
350100mc	■ 120"




ZONYX ADJUSTABLE SLANTED CEILING SUPPORT



Part Number	Description
350130mc	■ 14 1/4" - 24"
350140mc	■ 26 1/4" - 48"




ZONYX WALL SUPPORT



Part Number	Description
350150	■ 5-1/2" - 8-1/2"



ZONYX WALL SUPPORT II



Part Number	Description
-------------	-------------


350155	■ 14" - 24"
--------	-------------



ZONYX CANOPY POWER FEED

Part Number	Description
-------------	-------------

350115mc	■ 4"
----------	------



Technical


2400VA maximum
120VAC input

Suitable for dry location only
Mount to 3" - 4" round J-box
Switchable circuit breaker (1 - 25A)



ZONYX ADJUSTABLE POWER STEM

selective pendants, consult factory



Part Number	Description
-------------	-------------

350125mc	■ 7 1/2" - 11 1/2"
----------	--------------------

Technical

2400VA maximum
120VAC input

Suitable for dry location only
Mount to 3" - 4" round J-box
Switchable circuit breaker (1 - 25A)
Extendable from 13.88" - 24"



ZONYX CABLE POWER FEED

can be field shortened

Part Number	Description
-------------	-------------

350105mc	■ 10' cable
----------	-------------



Technical

2400VA maximum
120VAC input

Suitable for dry location only
Mount to 3" - 4" round J-box
Switchable circuit breaker (1 - 25A)
Shortenable cable




CURRENT LIGHTING CIRCUIT BREAKER

This power feed circuit breaker limits the allowable electrical load that can be put on the circuit. Approved by the California Energy Commission (Title 24) and required by USGBC.

Add the appropriate ordering code extension to the power feed part number. ie: 350115mc/020

Part Number	Description
/010	1 amp breaker
/020	2 amp breaker
/030	3 amp breaker
/050	5 amp breaker
/075	7.5 amp breaker
/100	10 amp breaker
/125	12.5 amp breaker

ZONYX UNI-PLUG STEP-DOWN ADAPTOR



Part Number	Description
350050mc	<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #808080; margin-right: 5px;"></div> matte chrome </div>

Technical
75VA maximum 120VAC input 11.7V AC output Suitable for dry location only Short circuit protection Overload protection Thermal protection Dimmable

